
Bahrain Fiber Optic Enterprise Router QSFP-DD




Overview

QSFP-DD is a new module and cage/connector system similar to current QSFP, but with an additional row of contacts providing for an eight lane electrical interface. It is being developed by the QSFP-DD MSA as a key part of the industry's effort to enable high-speed solutions. QSFP-DD extends the use. Quad Small Form-factor Pluggable Double Density (QSFP-DD) solution that fits into high-density switch and router client ports for optical interconnect links Powered by Greylock and Delphi DSP ASICs, and silicon photonic integrated circuits (PICs) for an optimized co-packaged design with 3D. Eoptolink's 400G QSFP56-DD transceivers are addressing the technical challenges of achieving high speed 400G interconnections. The transceivers have four optical lanes that operate at 100Gbps PAM4 modulation, providing solutions up to 400 Gbps. The transceivers have on the electrical side 8 lanes. Supporting the continuing growth in the bandwidth demand and datacenter traffic driven by networking and AI/ML requirements, the QSFP-DD (Double Density) Interconnect System delivers 8 lanes with up to 28 Gbps NRZ or 56 Gbps-PAM4 (up to 400 Gbps aggregate) in a compact footprint that is backward.

© 2026 Indzawo Optic Connect - All rights reserved


Bahrain Fiber Optic Enterprise Router QSFP-DD



They are operating on CWDM4 wavelength, and are compliant with the QSFP-DD MSA. Digital diagnostics functions are available via the I2C interface, as specified by the QSFP-DD MSA.



Multichannel AOCs combining our vertically integrated VCSEL array technology with standard QSFP and SFP+ connectors. They feature low power consumption, low weight, and a small bend radius for ...



QSFP-DD is a new module and cage/connector system similar to current QSFP, but with an additional row of contacts providing for an eight lane electrical interface. It is being developed by the QSFP-DD ...



Powered by Greylock and Delphi DSP ASICs, and silicon photonic integrated circuits (PICs) for an optimized co-packaged design with 3D Siliconization. Supports an expansive list of interoperability ...



This article explores how to interconnect OSFP and QSFP-DD ports in 400G/800G networks, covering key principles, form factor differences, and practical solutions for stable, high-speed data center ...

© 2026 Indzawo Optic Connect - All rights reserved

	QSFP-DD Interconnect System enables faceplate density equal to the current 2x1 QSFP form factor, but with 8-lane ports. In other words, a total of 256 differential pairs with 32 ports delivers double-lane ...
	It provides a QSFP-DD-to-QSFP-DD copper direct-attach solution. They are suitable for very short links and offer a cost-effective way to establish a 400-Gigabit link between QSFP-400G ports of ...
	Our QSFP-DD cages feature a proprietary heat sink design, making them the only solution to work in 15-18W applications at a low cost – providing superior thermal and signal integrity performance.
	QSFP-DD is a high-speed, high-density, hot-pluggable optical transceiver module used in data communication applications. QSFP-DD is an evolution of the QSFP (Quad Small Form Factor ...

© 2026 Indzawo Optic Connect - All rights reserved

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: https://www.indzawo.co.za
Email: sales@indzawo.co.za
Phone: +27 71 296 8473
Address: 22 Quantum Street, Midrand, 1685, Gauteng, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

© 2026 Indzawo Optic Connect - All rights reserved