

Bahrain Industrial-Grade Optical Switch 25G for Broadcast Transmis




This module provides 10G backward compatibility and simplifies network upgrade. It provides connectivity option for 25G Ethernet, 10G Ethernet and data center. It is fully compliant with the ...



It provides 25GBASE Ethernet connectivity option for 25G Ethernet, telecom and ...



It provides 25GBASE Ethernet connectivity option for 25G Ethernet, telecom and data center. Besides, this module offers interoperability, laying a foundation for the next-generation network upgrade. It is ...



The Telecommunications Regulatory Authority of the Kingdom of Bahrain approves that the equipment listed below is in compliance with the Regulation on the Approval and Importation of ...



The 25G SFP28 eSR optical transceiver module is designed for short-reach interconnections, such as within data center equipment or for 5G fronthaul applications.



The series uses 1 pair of multimode fiber optic transmission with a central wavelength of 850nm for distances up to 70m (OM3) or 100m (OM4), with an optional industrial grade operating temperature ...



Explore our diverse portfolio of 25G SFP28 optical transceivers, offering unparalleled compatibility, performance, and value. Enhance your network capabilities today by selecting our advanced optical ...



With 25 Gb/s capability over 10km of single-mode fibre, industrial-grade temperature tolerance, built-in monitoring and full standards compliance, it stands out as a compelling choice for ...



This series of products uses a pair of single-mode optical fiber for transmission, with a center wavelength of 1310nm, a distance of up to 30km (without FEC) or 40km (with FEC turned on), and ...



Our EDGEOPTIC 25G-SFP28-10I is a multi-vendor compatible industrial-grade 25GBASE-LR SFP28 dual-fiber optical module designed for 25 Gigabit Ethernet applications in harsh environmental ...



The Telecommunications Regulatory Authority of the Kingdom of Bahrain approves that the equipment listed below is in compliance with the Regulation on the ...



This series of products uses a pair of single-mode optical fiber for transmission, with a center wavelength of 1310nm, a distance of up to 30km (without FEC) or 40km (with FEC turned on), and ...



With industrial-grade design, low power consumption, and DOM support, it is ideal for data center interconnects, 25G Ethernet, and 5G wireless front-haul applications.

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.indzawo.co.za>

Email: sales@indzawo.co.za

Phone: +27 71 296 8473

Address: 22 Quantum Street, Midrand, 1685, Gauteng, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

