

## Distance between the suspended platform and the electrical distribution box



### Overview

Clearance: Electrical panels must be installed in a readily accessible area with a minimum clearance of 30 inches (762 mm) wide, 3 ft (36 inches or 914 mm) deep, and 6.5 feet ( $\approx$  2 meter) high in front of the panel. The panelboard's door (hinged cover) shall be able to be opened to a. As a licensed electrician, ensuring proper nec working clearance around electrical equipment is not just a matter of compliance—it's a fundamental requirement for safety and serviceability. Dedicated space: The space equal to the width and depth of electrical equipment in addition to the space extending. To re-cap Article #1 from March 5th and as required by OSHA, NFPA and the NEC: "working space around electrical enclosures or equipment shall be adequate for conducting all anticipated maintenance and operations safely, including sufficient space to ensure the safety of personnel working during. This guide is designed for professional electricians and electrical contractors with substantial practical experience and a working knowledge of electrical systems. It focuses on the clearance requirements for electrical gear and panels as outlined in the

National Electrical Code (NEC) 2023.

## Distance between the suspended platform and the electrical distrib



This document provides safety clearance recommendations for electrical panels. It includes tables outlining minimum clearance distances for various components of indoor and outdoor electrical panels.



Minimum clearances are established for work spaces in front of high voltage - electrical equipment such as switchboards, control panels, switches, circuit breakers, switchgear and motor controllers. These ...



If electrical equipment is being replaced, Condition 2 working space is permitted between dead-front switchboards, switchgear, panelboards, or motor control centers located across the aisle from each ...




The specific separation distance between a propane container's pressure relief valve and any electrical source of ignition depends on the container size and installation type.



Side clearance: There should be a minimum of 30 inches of clearance from the sides of all electrical equipment, but in no case less than the width of the equipment itself. This is referred to as the side-to ...




As demonstrated in this guide, the NEC 2023 provides specific and detailed standards for electrical gear and panel clearances that enhance safety during normal operation, maintenance, and ...



If electrical equipment is being replaced, Condition 2 working space is permitted between dead-front switchboards, switchgear, panelboards, or motor control centers located across the aisle from each ...



In addition to the 36-inch dimension (914 mm), the work space shall not be less than 30 inches (762 mm) wide in front of the electrical equipment and not less than the width of such equipment.



Clearance: Electrical panels must be installed in a readily accessible area with a minimum clearance of 30 inches (762 mm) wide, 3 ft (36 inches or 914 mm) deep, and 6.5 feet ( $\approx$  2 meter) high in front of ...



Per NEC 110.26 (D), all working spaces must have a minimum Electrical equipment headroom of 2.0 m (6 ft 6 in), measured from the floor or platform to the ceiling or any overhead obstruction like pipes or ...

## Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.indzawo.co.za>

Email: [sales@indzawo.co.za](mailto:sales@indzawo.co.za)

Phone: +27 71 296 8473

Address: 22 Quantum Street, Midrand, 1685, Gauteng, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

