


## Distribution boxes must not be stacked up



### Overview

According to OSHA 29 CFR 1910. 176 (b), the material must be properly protected against falling or collapsing and must not create a hazard. It must not block the access, the emergency exit or the emergency equipment. Where mechanical handling equipment is used, sufficient safe clearances shall be allowed for aisles, at loading docks, through doorways and wherever turns or passage must be made. Effective stacking in warehouses reduces the risk of falls, collapses, and struck-by incidents while improving overall efficiency and visibility. Recommended placement of each label is on the top center of each adjacent side. Labels bearing Intelligent Mail container barcodes must be affixed to the outside of any. While pallets make storage and transportation efficient, improper stacking creates serious hazards that can lead to worker injuries, property damage and costly OSHA violations.

## Distribution boxes must not be stacked up



OSHA regulates pallet storage under 29 CFR 1910.176 (b) which requires that materials stored in tiers must be stacked, blocked, interlocked and limited in height to remain stable and secure against ...




An elevated load shall not be tilted forward except when the load is in a deposit position over a rack or stack. When stacking or tiering, only enough backward tilt to stabilize the load shall be used.




Storage of material shall not create a hazard. Bags, containers, bundles, etc., stored in tiers shall be stacked, blocked, interlocked and limited in height so that they are stable and secure against sliding ...



- Goods must be well-packaged and completely enclosed without protruding parts in a fitted, durable and smooth outer packaging that can withstand normal cargo handling, consolidation, automated sorting ...



Safe stacking refers to the proper organization and placement of materials in a warehouse to prevent injuries, product damage, and compliance violations. Effective stacking in ...




Take care not to stack loads with corrugated boxes in areas where they could get wet, such as from roof leaks or condensation droplets. Do not stack them on a wet floor that could cause moisture to wick ...



Properly stacking pallets is integral to safety and efficiency in any warehouse or distribution center. Learn how to use the different stacking options safely!



All material must be stored and stacked correctly. It must not block the access, the emergency exit or the emergency equipment. The material must be prevented from slipping, ...



- Goods must be well-packaged and completely enclosed without protruding parts in a fitted, durable and smooth outer packaging that can withstand normal cargo handling, consolidation, automated sorting ...



For maximum visibility when transporting a load, do not stack mail higher than the top of the hamper, and to ensure ease of movement, do not load the hamper with more than 800 pounds.



Pallets may be stacked to a maximum of six tiers high, but must not exceed 84 inches in height (lower height restrictions may apply). Individual pallets must be strapped or shrinkwrapped (or both).

## Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.indzawo.co.za>

Email: [sales@indzawo.co.za](mailto:sales@indzawo.co.za)

Phone: +27 71 296 8473

Address: 22 Quantum Street, Midrand, 1685, Gauteng, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

