

Pin Dimensions of Slotted Optocoupler Module



Pin Dimensions of Slotted Optocoupler Module



I am changing from an Uno, to a Mega for my Coin Counter project. I am not quite sure what pins to use for fuor(4) of these: LM393 Chip Motor ...



This is a slotted Opto isolator module (MOC7811 or compatible), with an IR transmitter and a photodiode mounted inside. The module performs non-contact ...



Encoder sensors or also known as Slotted couplers and Opto-Interrupters are widely used for applications required to monitor any interruptions. The MOC module comes in a plastic molding that ...



The MOC-7811 Slotted Opto Isolator Module is a precision encoder sensor for non-contact object detection. Ideal for robotics, automation, and positional sensing, it offers reliable feedback and easy ...



The MOC7811 is an Encoder sensor or slotted coupler module or Photointerrupter Or Opto-interrupter used to monitor the interruptions. It comes with a top-mounted transmitter and ...



Share Tweet Pin it Description: Module Features:
Use imported groove coupler sensor Groove Width:
5mm Output state indicator lights Obscured output
high; unobstructed output low The comparator ...



Share Tweet Pin it Description: Module Features:
Use imported groove coupler sensor Groove Width:
5mm Output state indicator lights Obscured output
high; ...




LM393 Infrared Speed Sensor Module Optocoupler
Model: H2010 Optocoupler slot width : 10mm Main
chip: LM393 Working voltage: DC 5V PCB Mounting
holes distance: 15mm Screw Size: M3 Size: ...



□Description□ 4-pin module with the following
definitions: VCC (Power Positive), GND (Power
Negative), DO (Digital Output), AO (Inactive).
□Applications□ Widely used for motor speed ...



Learn how to use the Infrared Slotted Optical
Optocoupler Module with detailed documentation,
including pinouts, usage guides, and example
projects. Perfect for students, hobbyists, and ...



□Description□ 4-pin module with the following
definitions: VCC (Power Positive), GND (Power
Negative), DO (Digital Output), AO (Inactive).
□Applications□ Widely used for motor speed ...



Part Number: MOC7811 Function: Slotted Couplers / Interrupter Modules Package: Case 354A Manufacturer: Motorola Image Description Slotted couplers consist of an infrared emitting ...



Features: Use imported groove coupler sensor Groove Width: 5mm Output state indicator lights Obscured output high; unobstructed output low The comparator output, the signal is clean, the waveform, ...

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.indzawo.co.za>

Email: sales@indzawo.co.za

Phone: +27 71 296 8473

Address: 22 Quantum Street, Midrand, 1685, Gauteng, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

