

## Safe distance between ADSS optical cable and power line



### Overview

A safe distance must be maintained from power lines of different voltage levels: greater than 1. (1) ADSS optical cable installation is typically carried out on energized power line towers. This of course, allows for pole sharing, which of course, reduces installation costs and speeds-up deployment. 0 mm diameter, the maximum allowable span at 100 meters altitude is 300 meters under NESC light loading (0 Pa wind, 0 mm ice). At heavy loading conditions (1900 Pa wind, 12. The rated tensile strength. This procedure provides general information for installing all Corning Optical Communications Solo® ADSS All-Dielectric Self-Supporting fiber optic cables from 2-288 fibers.

## Safe distance between ADSS optical cable and power line



Determine the clearances between the proposed fiber optic cable plant and existing facilities on a case-by-case basis by referring to local safety codes, and your company's standard operating procedures.



ADSS cables enable aerial fiber to be installed close to power lines – how do they work and how can installers deploy them?



In this paper, models have been developed to study the safety of workers who maintain clean and contaminated ADSS cables in both wet and dry ...



A safe distance must be maintained from power lines of different voltage levels: greater than 1.0m for 35KV, greater than 1.5m for 110KV, and greater than 3.0m for 220KV.



The double swivel eye insures the ADSS cable will not see an induced torque as the pulling line enters and exits each traveler. A "flag" shall be attached just behind the swivel eye on the ...



This standard provides both construction and performance requirements for maintenance of the proper optical fiber integrity and optical transmission capabilities of ADSS cable.



Like other fiber optic cables, ADSS cable weighs less than equivalent copper cables and will tend to sag less over a given aerial span. Because of this, it should occupy the uppermost available ...




All-Dielectric Self Supporting (ADSS) cables can be erected in close proximity to power transmission lines. This of course, allows for pole sharing, which of course, reduces installation costs and speeds ...



4.3.2.6 The cable is not allowed to fall to the ground during the deployment process; it is necessary to keep the cable at a certain safe distance from its crossing objects.



AFL-ADSS® (All-Dielectric Self-Supporting) cable is ideal for installation in distribution as well as transmission environments, even when live-line installations are required.



For power lines up to 110 kV, a standard ADSS with an outer sheath thickness of 1.5 mm and tracking resistance of 2.5 kV/mm dry arcing distance works reliably. Above 110 kV up to 220 kV, choose an ...



The ADSS cable reel (pay-off) must be located directly in line with the first traveler and must be back from the structure four times the height of the traveler (4:1 distance to height ratio).



Purpose: This standard provides both construction and performance requirements for maintenance of the proper optical fiber integrity and optical transmission capabilities of ADSS cable. ...

## Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.indzawo.co.za>

Email: [sales@indzawo.co.za](mailto:sales@indzawo.co.za)

Phone: +27 71 296 8473

Address: 22 Quantum Street, Midrand, 1685, Gauteng, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

