

# Standard 1U chassis mounting hole spacing



## Overview

Vertical Hole Spacing: 1U equals 1. 1 mm) from the top or bottom of the U. Holes are grouped in sets of three, with each group representing one Rack Unit, commonly called 1U. The spacing is measured center-hole to center-hole and remains consistent whether the rack has square or round mounting holes. For the front and back vertical rails, the center-to-center hole. The TPS 1U Chassis (Art. BJ9900001) is a standard 19-inch rack mount power supply chassis designed for industrial applications, also known as the TPS 1U Chassis, BJ9900001, 19 inch 1U Chassis, Power Supply Chassis, Rack Mount Chassis, Industrial Chassis, Electronics Enclosure, Server Rack. To allow space between adjacent rack-mounted components, a panel is inch (0. If n is number of rack units, the ideal formula for panel height is  $h =$ . Standardization in rackmount systems is essential for ensuring equipment compatibility, optimal space utilization, and global product interoperability. These issues are reviewed below.

## Standard 1U chassis mounting hole spacing



Hole spacing and panel mounting This standard ensures dimensional alignment for rackmount servers, network switches, and other 1U/2U equipment used widely in data centers and ...



Vertical Hole Spacing: 1U equals 1.75 inches (44.45 mm), with three-hole sets repeating every 1.75 inches. Holes are centered at 0.25 inches (6.4 mm), 0.875 inches (22.2 mm), and 1.5 inches (38.1 ...



This specification outlines the sizing of server racks, including dimensions, mounting hole alignment, and spacing for consistent interoperability. Over time, this standard became the ...



Holes are grouped in sets of three, with each group representing one Rack Unit, commonly called 1U. Each U measures 1.75 inches (44.45 mm) vertically. The spacing is measured center-hole to center ...



White Cabinet

The vertical spacing between hole centers is standardized at 0.625 inches (15.875 mm), meaning three holes span exactly 1.25"—leaving 0.5" of margin above and below the equipment's ...



The mounting holes on rack rails are evenly spaced in groups of three — the total spacing for one U. This design makes it simple to align and secure any rack-mounted device.



With an overall dimension of 482.6mm width and approximately 671mm depth, this chassis ensures precise mounting with W2 mounting hole spacing of 465mm and H2 height direction mounting hole ...



It can also describe a unit that is 1U high and half the depth of a 4-post rack (such as a network switch, router, KVM switch, or server), such that two units can be mounted in 1U of space (one mounted at ...



Installing the system chassis in a rack mount enclosure requires some planning for issues such as location, spacing, airflow and power supply. These issues are reviewed below. EIA 310-D (RETMA) ...



Rack cabinets that meet EIA-310 standards have an alternating pattern of three holes per rack unit. For the front and back vertical rails, the center-to-center hole spacing begins at the top hole ...

## Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.indzawo.co.za>

Email: [sales@indzawo.co.za](mailto:sales@indzawo.co.za)

Phone: +27 71 296 8473

Address: 22 Quantum Street, Midrand, 1685, Gauteng, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

