

## Temperature setting for PE plastic extruder for optical cable sheathing



### Overview

Polyethylene (PE): Typically extruded between 180°C to 240°C. This range is ideal for ensuring the material's flexibility and durability. Our Recommendation Comments are closed. Suitable for sheathing of optical cables and wires and cables, the performance of KRD 2010 meets the relevant requirements of GB/T 15065-2009. The best extrusion performance can be obtained by using a PE screw extruder with a length-to-diameter ratio of 25:1 and a compression ratio of about 3. Due to its low dielectric loss, high dielectric strength low moisture take up, Polyethylene is widely used for wire & cable application. To further increase the temperature resistance, burning resistance, cut growth. Temperature isn't just a setting on your control panel—it's the driving force that determines how polymers melt, flow, and ultimately perform.

## Temperature setting for PE plastic extruder for optical cable sheath



To configure a Wire Extrusion Line correctly, you must first understand what happens inside the barrel. PE comes in various densities, primarily LDPE (Low Density), LLDPE (Linear Low), and HDPE (High ...



Master the art of temperature control in extrusion. This guide explains how precise barrel zone management is crucial for preventing material degradation and ensuring product quality.



Due to the differences in equipment from different manufacturers, the actual extrusion temperature needs to be adjusted based on therecommended process temperature according to the specific ...



This document provides processing guidelines for a moisture curable ...




To configure a Wire Extrusion Line correctly, you must first understand what happens inside the barrel. PE comes in various densities, primarily LDPE (Low Density), ...




Proper heating and cooling ensure smooth plastic flow, prevent defects, and enhance the durability of extruded cables. This guide explores the mechanisms, components, and best ...



This document provides processing guidelines for a moisture curable crosslinkable polyethylene compound for low voltage power cable insulation. Key points include: 1. The compound cures after ...



Proper heating and cooling ensure smooth plastic flow, prevent defects, and enhance the durability of extruded cables. This guide explores the ...



In the extrusion process Polyethylene has a melting point range of 120 to 180 degrees Celsius for medium to high density PE and 105 to 115 degrees Celsius for low-density polyethylene. The good ...



Polyethylene (PE): Typically extruded between 180°C to 240°C. This range is ideal for ensuring the material's flexibility and durability.  
Polypropylene (PP): Requires temperatures around ...



Initial parameterization of the zone temperatures of the extruder: The typical procedure for the initial setting of the temperature profile is usually based on various material-specific parameters ...



Master the art of temperature control in extrusion. This guide explains how precise barrel zone management is crucial for preventing material ...



Note: This is meant as a general guide. Please consult your material and machinery representative. Our Recommendation. Comments are closed.



In the extrusion process Polyethylene has a melting point range of 120 to 180 degrees Celsius for medium to high density PE and 105 to 115 degrees Celsius ...



Low Temperature Flexibility- At very low temperatures, the wire & cable materials should not lose flexibility or become brittle, causing crack while remaining in a bent condition.

## Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.indzawo.co.za>

Email: [sales@indzawo.co.za](mailto:sales@indzawo.co.za)

Phone: +27 71 296 8473

Address: 22 Quantum Street, Midrand, 1685, Gauteng, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

