


What is the spacing between cable trays in a vertical shaft



Overview

In general, vertical spacing for cable trays should be 30 cm (12 in), measured from the bottom of the upper tray to the top of the lower tray. The NEC has a requirement for ladder-type cable trays. The rungs cannot be more. Clearances: Maintain at least 12 inches of vertical clearance above trays for installation and maintenance access (2026 NEC update). Separation of Electrical and Instrumentation Cables Electrical on Top, Instrumentation Below: Typically, electrical trays are positioned above instrumentation trays. It is used in EPC projects for basic engineering, detailed engineering, making the bill of quantities (BOQ), and. In vertical trays, cables shall also be secured at intermediate locations as necessary to keep all cables completely within and secured to the tray.

What is the spacing between cable trays in a vertical shaft



The 2026 NEC introduced an important update: cable trays must have at least 12 inches of clear vertical space above them to allow for installation and maintenance access.



In vertical trays, cables shall also be secured at intermediate locations as necessary to keep all cables completely within and secured to the tray." So, it is no indication what could be the ...



At least 12 inches of clear space should be provided between tray levels. We also add that instrument trays cross electrical trays at 90 degrees if the 12 inch rule "gets violated".



Spacing Standards: Electrical (power) and instrumentation (signal/control) cable trays should maintain a minimum vertical and horizontal distance. Industry standards often recommend at least 300mm (12 ...



Vertically running cable trays in cable riser/shaft shall be supported at an interval of 1000 mm. In case cables are to be laid over the top of switchgear panels, a clearance of 300 mm shall be maintained.




Cable trays may be installed in virtually every professional structure, including large factories and high office towers. Their utilization is only possible in environments that have a lot of ...



According to ABB's technical guide, the type of tray and the space between the rungs impact how well it works for small control cables and large power conductors. Enter the width and ...



Explore the essential cable tray support spacing requirements for safe and efficient installations. Learn NEC guidelines for perforated, ladder, and wire mesh trays.



Ladder cable tray is available in widths of 6, 9, 12, 18, 24, 30, 36, 42 and 48 inches with rung spacings of 6, 9, 12 or 18 inches. Note that wider rung spacings and wider cable tray widths decrease the overall ...



In general, vertical spacing for cable trays should be 30 cm (12 in), measured from the bottom of the upper tray to the top of the lower tray. A minimum clearance of 23 cm (9 in) should be ...

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.indzawo.co.za>

Email: sales@indzawo.co.za

Phone: +27 71 296 8473

Address: 22 Quantum Street, Midrand, 1685, Gauteng, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

