Indzawo Optic Connect

What size should the cable tray nut be




Overview

The 5/16" spring nut (BB200) is the recommended size to use with all the Zip cable tray accessories. These channel nuts have a short spring for use in channel up to 7/8" (22mm) thick. maintain spacing or to keep cables in place when the tray is ect the minimum bend ra-dius for cables as they exit the bottom of the cable tray. A rung spacing of 6 to 9 inches (150 to 230 mm) is preferable when the cable tray cont d for instrumentation and control applications that require. Runway Hold-Down Clamp Kit, Height: 1-1/2", Width: 2", Depth 2. 53", Material: Steel, Finish: Black Powder Coat. Use two CE40 and one EZBN14EZ (0445225) to make a complete. Specials quoted per customer print. / Size Dia C 3/8" 1-7/16" 3/8" 27 1/2" 1-3/8" 3/8" 45 Rod Stock Wt. Per Bundle Hubbell's NEXTFRAME® Ladder Tray is the effective and widely used cable runway that supports and delivers bundles of cable between cabinets, racks, and closets, along walls, and suspended from ceilings. The Ladder Tray features light, rugged, tubular steel construction. Manufactured from high-quality steel and finished with a zinc plating, this tray nut offers excellent resistance to corrosion and wear.

© 2026 Indzawo Optic Connect - All rights reserved

What size should the cable tray nut be



Simply insert anywhere along the length of the cable tray siderail to fasten all accessories. Fits in the rung of the BW, BX, BY & BZ Series cable trays for added flexibility. The 5/16" spring nut (BB200) is ...



Some applications may require the cable tray to support the weight of a single, dead object in addition to the cable loads. Specifications typically require this to be applied at the midpoint of the span between ...



When fitting cable trays and their accessories, the products are cut on site to create changes of direction, adjust sections, etc. Damage can also occur during handling; as a result, both the ...



The choice of method should be discussed with a local inspector. The best decision may be to extend only the cables, creating a discontinuity in the cable tray.



We will first explain standard cable tray dimensions used across the industry, then examine how dimensions vary by tray type, and finally show how to ...

© 2026 Indzawo Optic Connect - All rights reserved




Each Cable Tray System includes a range of factory manufactured bends, tees, reducers etc. that are unique to the sizes and ranges that incorporate fast fix integral couplers for a better fit and quicker ...



Two-piece bracket attaches to 3/8" (9.5mm) wide x 1 1/2" (38.1mm) or 3/8" (9.5mm) wide x 2" (50.8mm) ladder rack rail. Bracket halves slide into position and clamp together on the ladder rack rail, which ...



We will first explain standard cable tray dimensions used across the industry, then examine how dimensions vary by tray type, and finally show how to calculate and select the correct ...



The M6 x 16mm cable tray bolt & flange nut set provides secure fastening support for cable trays and channel systems with minimal surface obstruction. Each set includes a fully threaded M6 truss head ...



Description The Rexel Tray Nut 10mm Steel Zinc Plated LTNUT is a highly durable and reliable fastening solution designed for use in electrical and construction projects. Manufactured from high ...



We recommend that covers on vertical cable tray runs to a height of 6 ft. (1.83 m) to 8 ft. (2.44 m) above the floor to both isolate cables and personnel. Cover clamps are not included with the cover and ...

© 2026 Indzawo Optic Connect - All rights reserved

	1/2-13 Spring Nuts w/ Spring (2.50), No Shrink, Thick w/ Spring (1.50), Shrink Wrap w/ Spring (.75), No Shrink, Thin No Spring, No Shrink No Spring, No Shrink, Thin 5/8-11

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: https://www.indzawo.co.za
Email: sales@indzawo.co.za
Phone: +27 71 296 8473
Address: 22 Quantum Street, Midrand, 1685, Gauteng, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

© 2026 Indzawo Optic Connect - All rights reserved